## **Forced Air Oven**

Capacity

Interior Dimensions W x D x H

42.5" x 34.1" x 85.9" Exterior Dimensions W x D x H 1080 x 866 x 2182 mm

**Unit Weight** 569.4 lb (258.3 kg) **Shipping Weight** 694 lb (315 kg) 6 standard, 9 total **Shelves** 75 lb / 34 kg Maximum Weight Per Shelf **Permitted Total Load** 

Standard Door Gasket Woven Fiberglass

**Access Port** Watlow EZ-ZONE Controls

Warranty Interior Construction 300 series stainless steel **Exterior Construction** 20 gauge steel, powder coated

Vertical Clearance 24.0" (600 mm) Wall Clearance, Each Side

Wall Clearance, Rear 12.0" (300 mm)

Electrical, 50/60Hz, AC, 1Ø

Voltage 50 Full Load Amps Nominal Power (watts @150°C) 6500

At 80°C 48.1 At 150°C 108.8 At 306°C 243.8

Heat-Up Time — Minutes to 306°C 31 Recovery after Door Opening (30 sec.) — Minutes to 80°C 3 Recovery after Door Opening (30 sec.) — Minutes to 150°C 3

5 Recovery after Door Opening (60 sec.) — Minutes to 80°C Recovery after Door Opening (60 sec.) — Minutes to 150°C 5.5

At 80°C At 150°C 2.5

Air Changes Per Hr at Max 125.0 Flow Rate (CFM) 17.3

**TFO-28** PART ID: CTF2822-H

28 cu.ft. (792 liters)

317" x 26 0" x 60 9" 805 x 660 x 1546 mm

450 lb / 204 kg

2.75" Rear

2 Year Limited Warranty

6.0" (152 mm)

6



Direct Hardwire ✓

Energy Consumption (kWh/day)

Heat-Up Time — Minutes to 80°C

Temperature Range 15°C above ambient to 306°C

Heat-Up Time — Minutes to 150°C 15 Recovery after Door Opening (30 sec.) — Minutes to 306°C 5

Recovery after Door Opening (60 sec.) — Minutes to 306°C 10

**Temperature Uniformity** 

1.5 At 306°C 5.5

**Air Flow Performance** 









0740580 6/22

